

2016
Virginia Department of Transportation
Daily Traffic Volume Estimates
Including Vehicle Classification Estimates

where available

Special Locality Report

130

Town of South Boston

Information in this report is included in Report

41

(Halifax County)

Prepared By
Virginia Department of Transportation
Traffic Engineering Division

In Cooperation With
U.S. Department of Transportation
Federal Highway Administration

Virginia Department of Transportation
Traffic Engineering Division
Traffic Monitoring Section

The Virginia Department of Transportation (VDOT) conducts a program where traffic count data are gathered from sensors in or along streets and highways and other sources. From these data, estimates of the average number of vehicles that traveled each segment of road are calculated. VDOT periodically publishes booklets listing these estimates.

One of these booklets, titled "Average Daily Traffic Volumes with Vehicle Classification Data, on Interstate, Arterial and Primary Routes" includes a list of each Interstate and Primary highway segment with the estimated Annual Average Daily Traffic (AADT) for that segment. AADT is the total annual traffic estimate divided by the number of days in the year. This booklet also includes information such as estimates of the percentage of the AADT made up by 6 different vehicle types, ranging from cars to double trailer trucks; estimated Annual Average Weekday Traffic (AAWDT), which is the number of vehicles estimated to have traveled the segment of highway during a 24 hour weekday averaged over the year; as well as Peak Hour and Peak Direction factors used by planners to formulate design criteria.

In addition to the Primary and Interstate publication, one hundred books are published periodically, one for each of 100 areas across the state defined by VDOT for record-keeping purposes. These books include traffic volume estimates for roads within the county, cities, and towns within the area. These books are titled "Daily Traffic Volumes Including Vehicle Classification Estimates, where available; Jurisdiction Report numbers 00 through 99".

Also available are a number of reports summarizing the average Vehicle Miles Traveled (VMT) in selected jurisdictions and other categories of highways. There are many different ways to present traffic volume summary information. Because the user determines the value of each presentation, the reports have been redesigned based on user requests and feedback. The people of the VDOT Traffic Engineering Division Traffic Monitoring Section who produce these books welcome requests for other helpful ways of presenting the summary information.

A compact disc (CD) is available that includes files in the Adobe® Portable Document Format (PDF) that can be displayed, searched, and printed using common desktop computer equipment. The CD includes the publications described above as well as a number of other reports, including specialized VMT summaries and smaller AADT reports for each city and town separately.

Publication Notes

Parallel Roads

For road inventory and management purposes, some roadways are counted separately by direction and have separately published traffic estimates for each direction of travel. Examples of such roadways are the interstate system and routes with separated facilities and (usually) one-way traffic facilities in urban areas. In these publications, they are referred to as parallel roads. As a convenience for the users of the publication, the listing for segments of roads with parallel segments are published with both the traffic estimates for their own direction of travel (e.g. I-95 Northbound) as well as the estimate of the total of all traffic on the same route including parallel roadways (all directions of I-95). The publication will have a "Combined Traffic Estimates for Parallel Roadways on this Route" or "Combined Traffic" identifiers for the combined direction of travel estimates.

Roadways such as I-395 with a North segment, a South segment and a separate Reversible lane segment will have the estimate for more than two parallel roadways included in the entire combined traffic estimate.

Some routes have very complicated paths through cities and towns. These parallel paths may be too complex to allow a relationship between nearby sections of the opposite direction on the same route. In this case, to indicate that the traffic estimates for such a road segment may not include all directions of traffic on that route, the line that would list the combined values will indicate "NA" for not available.

VDOT's traffic monitoring program includes more than 100,000 segments of roads and highways ranging from several mile sections of Interstate highways to very short sections of city streets. Due to problems experienced obtaining some traffic count data, and the level of quality necessary to maintain confidence in the data, no estimate is currently available for some segments of roadway. These segments are included in the publications indicating "NA" for not available. It is the intention of the VDOT Traffic Engineering Division Traffic Monitoring group to obtain the data necessary and to report traffic volume estimates on all road segments included in these publications.

Many of the road segments in this program are local secondary roads. The amount and detail of data collected on these roads are not as great as the data collected on higher volume roads. The vehicle classification, average weekday traffic volumes, and the theoretical design hour traffic volumes are not calculated for these roads. The publications indicate "NA" for the information that is not available.

This publication is based on a traffic monitoring program initiated in 1997. Because the data collection techniques and statistical evaluation processes are different than those used in previous years, comparison with previous publications may be misleading.

Glossary of Terms:

Route: The Route Number assigned to this segment of roadway with the master inventory route number if this is an overlapping route, with official street or highway name if available.

Length: Length of the traffic segment in miles.

AADT: Annual Average Daily Traffic. The estimate of typical daily traffic on a road segment for all days of the week, Sunday through Saturday, over the period of one year.

QA: Quality of AADT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- H Historical Estimate
- M Manual Uncounted Estimate
- N AADT of Similar Neighboring Traffic Link
- O Provided By External Source
- R Raw Traffic Count, Unfactored

4Tire: Percentage of the traffic volume made up of motorcycles, passenger cars, vans and pickup trucks.

Bus: Percentage of the traffic volume made up of busses.

2Axle Truck: Percentage of the traffic volume made up of 2 axle single unit trucks (not including pickups and vans).

3+Axle Truck: Percentage of the traffic volume made up of single unit trucks with three or more axles.

1Trail Truck: Percentage of the traffic volume made up of units with a single trailer.

2Trail Truck: Percentage of the traffic volume made up of units with more than one trailer.

QC: Quality of Classification Data:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- C Short Term Classified Traffic Count Data
- F Factored Short Term Traffic Count Data
- H Historical Estimate
- M Mass Collective Average
- N Classification Estimates of Similar Neighboring Traffic Link

K Factor: The estimate of the portion of the traffic volume traveling during the peak hour or design hour.

QK: Quality of the K Factor estimate:

- A Factor based on 30th Highest Hour Observed During at least 250 days of Continuous Traffic Data
- B Factor based on other Hour Observed During Less than 250 days of Continuous Traffic Data
- F Factor based on Highest Hour Collected at in a 48 Hour Weekday Period
- M Factor based on Manual Estimate of design hour
- N Design Hour Factor (K Factor) of Similar Neighboring Traffic Link
- O Provided by External Source

Dir Factor: The estimate of the portion of the traffic volume traveling in the peak direction during the peak hour..

AAWDT: Average Annual Weekday Traffic. The estimate of typical traffic over the period of one year for the days between Monday through Thursday inclusive.

QW: Quality of AAWDT:

- A Average of Complete Continuous Count Data
- B Average of Selected Continuous Count Data
- F Factored Short Term Traffic Count Data
- G Factored Short Term Traffic Count Data with Growth Element
- M Manual Uncounted Estimate
- N AAWDT of Similar Neighboring Traffic Link
- O Provided by External Source

Year: Year for which the published values are appropriate. If the Quality of AADT (QA) is "R", the year is the year that the raw traffic count was collected, and if available,

Route Shield Legend

Route Systems

- North
 Interstate Route Traffic volume data for Interstate Routes and some other routes are reported separately by direction, as well as combined.
-  US Route
-  Virginia State Route
-  Frontage Road (F precedes frontage route number)
-  Secondary Route

Special Routes

- Bus
 Bus - Business Route
Bypass - Bypass Route
Truck - Truck Route
- ALT
 ALT - Alternate Route
Wve - Wve Route connector
-  P - Parallel Route; Southbound or Westbound direction lanes of a numbered route where they are on a different road facility than the other direction.
-  The VDOT Maintenance Jurisdiction number is displayed below the Secondary Route Number if the Maintenance Jurisdiction is different than the jurisdiction in the title of the report.


Virginia Department of Transportation
Traffic Engineering Division
2016
Annual Average Daily Traffic Volume Estimates By Section of Route
Town of South Boston

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW
							2Axle	3+Axle	1Trail	2Trail						
34 Hodges St	From: North Main St															
	Town of South Boston	0.54	2000	G	98%	1%	1%	0%	0%	0%	C	0.099	0.556	2100	G	
	To: US 360 John Randolph Blvd															
58 360 Bill Tuck Hwy	From: US 501 Huell Matthews Hwy															
	Town of South Boston	0.18	13000	G	86%	1%	1%	1%	12%	0%	F	0.077	0.549	13000	G	
	To: ECL South Boston															
129 North Main St	From: US 501 P; Wilborn Ave; Main St															
	Town of South Boston	0.09	3500	G	99%	1%	0%	0%	0%	0%	F	0.090	0.799	3700	G	
	To: US 501 Broad St															
129 North Main St	From: SR 34 Hodges St															
	Town of South Boston	0.38	5500	G	99%	1%	0%	0%	0%	0%	C	0.094	0.586	5900	G	
	To: Edmunds St															
129 North Main St	From: College St															
	Town of South Boston	0.16	6600	G	99%	1%	0%	0%	0%	0%	F	0.095	0.51	7000	G	
	To: Hamilton Blvd															
129 North Main St	From: NCL South Boston															
	Town of South Boston	0.19	7100	G	99%	1%	0%	0%	0%	0%	F	0.098	0.523	7500	G	
	To: US 501 P; Main St															
129 North Main St	From: US 501 Broad St															
	Town of South Boston	0.63	6600	G	99%	1%	0%	0%	0%	0%	F	0.098	0.513	7000	G	
	To: US 501 Broad St															
129 North Main St	From: Marshall St															
	Town of South Boston	0.88	12000	G	99%	1%	0%	0%	0%	0%	C	0.094	0.516	12000	G	
	To: US 501 P; Main St															
304 Seymour Dr	From: US 501 Broad St															
	Town of South Boston	0.08	2900	G	95%	1%	1%	2%	1%	0%	F	0.091	0.603	3100	G	
	To: Marshall St															
304 Seymour Dr	From: US 360 John Randolph Blvd															
	Town of South Boston	0.38	3000	G	95%	1%	1%	2%	1%	0%	C	0.100	0.516	3200	G	
	To: US 501 Riverdale															
360 58 Bill Tuck Hwy	From: CL South Boston															
	Town of South Boston	0.18	13000	G	86%	1%	1%	1%	12%	0%	F	0.077	0.549	13000	G	
	To: SCL South Boston															
360 John Randolph Blvd	From: SR 304 Seymour Dr															
	Town of South Boston (Maint: 41)	0.16	11000	G	87%	1%	1%	2%	10%	0%	F	0.084	0.518	10000	G	
	To: SR 34 Hodges St															
360 John Randolph Blvd	From: Hamilton Blvd															
	Town of South Boston	0.52	12000	G	87%	1%	1%	2%	10%	0%	F	0.081	0.673	11000	G	
	To: US 501 P; Main St															
360 John Randolph Blvd	From: ECL South Boston															
	Town of South Boston (Maint: 41)	0.44	13000	G	87%	1%	1%	2%	10%	0%	F	0.086	0.564	13000	G	
	To: US 501 P; Main St															
360 John Randolph Blvd	From: US 501 P; Main St															
	Town of South Boston (Maint: 41)	0.09	8700	G	87%	1%	1%	2%	10%	0%	F	0.085	0.641	8700	G	
	To: ECL South Boston															

Virginia Department of Transportation
Traffic Engineering Division
2016
Annual Average Daily Traffic Volume Estimates By Section of Route
Town of South Boston

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW
							2Axle	3+Axle	1Trail	2Trail						
501 Main St	From: US 58, US 360; SCL South Boston															
	Town of South Boston	0.53	19000	G	86%	1%	1%	3%	9%	0%	F	0.088	0.54	20000	G	
501 Broad St	To: US 501 P; Broad St															
	Town of South Boston	0.09	9300	G	97%	0%	1%	0%	2%	0%	F	0.091	0.539	9900	G	
Combined Traffic Estimates for 2 Parallel Roadways on this Route:			17000	G	97%	1%	1%	0%	2%	0%	F	0.091	F	0.767	18000	G
501 Broad St	To: SR 304 Seymour Dr															
	Town of South Boston	0.22	8800	G	97%	0%	1%	0%	2%	0%	C	0.099		9300	G	
Combined Traffic Estimates for 2 Parallel Roadways on this Route:			17000	G	97%	1%	1%	0%	2%	0%	C	0.089	F	0.518	18000	G
501 Broad St	To: SR 129 North Main St															
	Town of South Boston	0.26	6800	G	97%	0%	1%	0%	2%	0%	F	0.086		7300	G	
Combined Traffic Estimates for 2 Parallel Roadways on this Route:			15000	G	96%	1%	1%	0%	2%	0%	F	0.09	F	0.511	16000	G
501 Broad Street	To: Third St															
	Town of South Boston	0.18	6600	G	96%	1%	1%	1%	2%	0%	C	0.088		7000	G	
Combined Traffic Estimates for 2 Parallel Roadways on this Route:			17000	G	96%	1%	1%	0%	2%	0%	F	0.085	F	0.52	18000	G
501 Broad Street	To: Edmunds St															
	Town of South Boston	0.41	6600	G	96%	1%	1%	1%	2%	0%	F	0.087		7000	G	
Combined Traffic Estimates for 2 Parallel Roadways on this Route:			17000	G	96%	1%	1%	0%	2%	0%	F	0.084	F	0.518	18000	G
501 Wilborn Ave	To: US 501 P; Wilborn Ave															
	Town of South Boston	0.51	16000	G	96%	1%	1%	1%	2%	0%	F	0.093	0.502	17000	G	
501 Halifax Rd	To: Hamilton Blvd															
	Town of South Boston	0.69	17000	G	96%	1%	1%	1%	2%	0%	F	0.092	0.523	18000	G	
501 Halifax Rd	To: Old NCL South Boston															
	Town of South Boston	0.79	18000	G	96%	1%	1%	1%	2%	0%	F	0.090	0.554	20000	G	
501 Halifax Rd	To: SR 129 N, Old Halifax Rd															
	Town of South Boston	0.38	20000	G	96%	1%	1%	1%	2%	0%	F	0.089	0.54	21000	G	
501 Main St	To: NCL South Boston															
	Town of South Boston	0.07	7900	G	96%	1%	1%	0%	2%	0%	F	0.091		8400	G	
Combined Traffic Estimates for 2 Parallel Roadways on this Route:			17000	G	97%	1%	1%	0%	2%	0%	F	0.091	F	0.767	18000	G
501 Main St	To: SR 304 Seymour Dr															
	Town of South Boston	0.18	8200	G	96%	1%	1%	0%	2%	0%	C	0.089		8800	G	
Combined Traffic Estimates for 2 Parallel Roadways on this Route:			17000	G	97%	1%	1%	0%	2%	0%	C	0.089	F	0.518	18000	G
501 Wilborne Ave	To: SR 129 North Main St															
	Town of South Boston	0.26	8100	G	96%	1%	1%	0%	2%	0%	F	0.09	0.901	8700	G	
Combined Traffic Estimates for 2 Parallel Roadways on this Route:			15000	G	96%	1%	1%	0%	2%	0%	F	0.09	F	0.511	16000	G
501 Main St	To: Third St															

Virginia Department of Transportation
 Traffic Engineering Division
 2016
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Town of South Boston

Route	Jurisdiction	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW
							2Axle	3+Axle	1Trail	2Trail						
	From:	Third St														
 Wilborne Ave	Town of South Boston	0.57	10000	G	96%	1%	1%	0%	2%	0%	F	0.085		0.807	11000	G
Combined Traffic Estimates for 2 Parallel Roadways on this Route:			17000	G	96%	1%	1%	0%	2%	0%	F	0.085	F	0.519	18000	G
	To:	US 501 Broad Street														

Virginia Department of Transportation
Traffic Engineering Division
2016
Annual Average Daily Traffic Volume Estimates By Section of Route
Town of South Boston

Route	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year	
						2Axle	3+Axle	1Trail	2Trail								
Town of South Boston																	
① Railroad Ave	0.36	720	G	97%	0%	1%	2%	0%	0%	C	0.104		0.581	760	G	2016	
						From: Edmunds St											
						To: Summit Dr											
① Railroad Avenue	0.18	890	G	97%	0%	1%	2%	0%	0%	F	0.098		0.602	940	G	2016	
						From: Seymour Dr											
						To: Seymour Dr											
② Riley Ave	0.16	930	G	98%	1%	1%	0%	0%	0%	C	0.100		0.510	990	G	2016	
						From: Vaughan St											
						To: Vaughan St											
③ Seymour Dr	0.11	740	G	97%	0%	1%	2%	0%	0%	C	0.124		0.543	790	G	2016	
						From: Ferry St											
						To: Watkins Ave											
④ Vaughan St	0.35	1000	G	98%	1%	1%	1%	0%	0%	C	0.099		0.539	1100	G	2016	
						From: Riley Ave											
						To: Pine Ave											
⑤ Webster St	0.61	940	G	97%	1%	1%	1%	0%	0%	C	0.089		0.506	1000	G	2016	
						From: Wilborn Ave											
						To: North Main St											
⑥ Third St	0.14	470	G	97%	1%	1%	0%	1%	0%	C	0.125		0.660	500	G	2016	
						From: US 501; Broad St											
						To: IUS 501-P Wilborn Ave											
④700 Berry Hill Rd	1.13	1900	G	98%	0%	1%	0%	0%	0%	C	0.098		0.52	2000	G	2016	
						From: WCL South Boston											
						To: Wilmoth Ave											
④700 Berry Hill Rd	0.20	2800	G	98%	0%	1%	0%	0%	0%	F	0.089		0.527	3000	G	2016	
						From: Summit Dr											
						To: Summit Dr											
④700 Edmunds St	0.06	3100	G	98%	0%	1%	0%	0%	0%	F	0.083		0.520	3300	G	2016	
						From: Railroad Ave											
						To: Railroad Ave											
④700 Edmunds St	0.45	2000	G	98%	0%	1%	1%	0%	0%	C	0.086		0.553	2100	G	2016	
						From: US 501; Wilborn Ave											
						To: US 501 Wilborn Ave											
④700 Edmunds St	0.54	1400	G	96%	1%	2%	1%	0%	0%	C	0.092		0.519	1500	G	2016	
						From: SR 29; North Main St											
						To: Seymour Dr											
④701 Marshall Ave	0.15	740	G	98%	1%	1%	1%	0%	0%	F	0.183		0.509	790	G	2016	
						From: Fenton St											
						To: Fenton St											
④701 Marshall Ave	0.41	850	G	98%	1%	1%	1%	0%	0%	C	0.127		0.5	900	G	2016	
						From: Hodges St											
						To: Hodges St											
④702 Hamilton Blvd	0.37	3100	G	99%	0%	0%	0%	0%	0%	C	0.095		0.578	3300	G	2016	
						From: SCL South Boston											
						To: Wilborn Ave											
④702 Hamilton Blvd	0.70	5900	G	93%	1%	1%	1%	4%	0%	C	0.105		0.521	6300	G	2016	
						From: SR 129 North Main St											
						To: SR 129 North Main St											
④702 Hamilton Blvd	1.26	8000	G	95%	1%	1%	1%	3%	0%	C	0.109		0.582	8600	G	2016	
						From: US 360 John Randolph Blvd											
						To: US 360 John Randolph Blvd											
④704 College St	0.80	1000	G	99%	1%	0%	0%	0%	0%	C	0.102		0.505	1100	G	2016	
						From: North Main St											
						To: Cavalier Blvd											
④710 Jeffress St	0.20	740	G	97%	1%	1%	0%	0%	0%	C	0.105		0.592	790	G	2016	
						From: North Main St											
						To: Fenton St											
④710 Fenton St	0.19	490	G	99%	1%	0%	0%	0%	0%	C	0.111		0.719	520	G	2016	
						From: Jeffress St											
						To: Marshall Ave											
④713 Watkins Ave	0.61	2000	G	96%	1%	1%	1%	0%	0%	C	0.096		0.505	2100	G	2016	
						From: Edmunds St											
						To: Seymour Dr											

Virginia Department of Transportation
 Traffic Engineering Division
 2016
 Annual Average Daily Traffic Volume Estimates By Section of Route
 Town of South Boston

Route	Length	AADT	QA	4Tire	Bus	-----Truck-----				QC	K Factor	QK	Dir Factor	AAWDT	QW	Year
						2Axle	3+Axle	1Trail	2Trail							
Town of South Boston																
Carrington St		NA				From Watkins Ave				NA				NA		
						To Noblin Ave										
College St		500	G			From Llewellyn Avenue				0.100		0.626	500	G	2016	
						To Washington Avenue										
Greenway Dr		360	G			From Wilborn Ave				0.109		0.738	360	G	2016	
						To Norwood Ave										
Ridge St		290	G			From Spring Avenue				0.124		0.622	290	G	2016	
						To Alderson Avenue										
Robin Hood Rd		430	G			From Halifax Rd				0.107		0.638	430	G	2016	
						To Nottingham Dr										